


Data Sheet



Belts

CS 310 X



Applications

Stainless steel
Wood
Steel
NF metals
Plastic

Properties

- Bonding agent Resin
- Aluminium
- Grain oxide
- Coating Close
- Backing X-cotton

Available grits

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000

Width in mm	Length in mm	Cat.number	Belt joint	Grit
25.0	1065.0	244635	F4G	60
25.0	1065.0	244634	F4G	80
50.0	1020.0	47753	F5	40
50.0	1020.0	48549	F5	60
50.0	1020.0	49300	F5	80
50.0	2000.0	4587	F4G	40
50.0	2000.0	4590	F4G	60
50.0	2000.0	4591	F4G	80
50.0	2000.0	4593	F4G	120
75.0	2000.0	4594	F4G	36
75.0	2000.0	4595	F4G	40
75.0	2000.0	4596	F4G	60
75.0	2000.0	49399	F4G	80
75.0	2000.0	50652	F4G	120
75.0	2000.0	51222	F4G	180
75.0	2000.0	51470	F4G	240
100.0	920.0	48717	F5	60
100.0	920.0	49454	F5	80

100.0	920.0	50136	F5	100
150.0	2000.0	47492	F4G	36
150.0	2000.0	47921	F4G	40
150.0	2000.0	48821	F4G	60
150.0	2000.0	49581	F4G	80
150.0	2000.0	50767	F4G	120
200.0	550.0	170543	F7G	24
200.0	550.0	97832	F7G	40
200.0	550.0	105992	F7G	60
200.0	550.0	123929	F7G	80
200.0	550.0	123931	F7G	120
200.0	750.0	47101	F7G	24
200.0	750.0	47561	F7G	36
200.0	750.0	48028	F7G	40
200.0	750.0	48970	F7G	60
200.0	750.0	49764	F7G	80
200.0	750.0	50340	F7G	100
200.0	750.0	50872	F7G	120