

Data Sheet



Fibre Discs

CS 565



Applications

Stainless steel
Steel
Metals

Properties

- Bonding agent Resin
- Zirconia
- Grain alumina
- Coating Close

Available grits

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

Cat.number	Diameter in mm	Hole	Hole Form	Grit
23680	100.0	16	10	36
84604	100.0	16	10	60
188678	100.0	16	10	80
93409	115.0	22	10	24
65698	115.0	22	10	36
242800	115.0	22	10	40
85517	115.0	22	10	50
65700	115.0	22	10	60
65701	115.0	22	10	80
95335	115.0	22	30	24
6686	115.0	22	30	36
242801	115.0	22	30	40
92066	115.0	22	30	50
6687	115.0	22	30	60
6688	115.0	22	30	80
204609	115.0	22	30	100
95071	125.0	22	10	24
65681	125.0	22	10	36

242802	125.0	22	10	40
65707	125.0	22	10	60
23001	125.0	22	10	80
97643	125.0	22	30	24
6620	125.0	22	30	36
242803	125.0	22	30	40
93054	125.0	22	30	50
6721	125.0	22	30	60
23005	125.0	22	30	80
204611	125.0	22	30	100
65702	180.0	22	10	36
65705	180.0	22	10	60
65706	180.0	22	10	80
95993	180.0	22	30	24
65703	180.0	22	30	36
242807	180.0	22	30	40
93045	180.0	22	30	50
6690	180.0	22	30	60
6691	180.0	22	30	80