

PROFESSIONAL CONSTRUCTION & INDUSTRIAL PRODUCTS

FIX ALL HIGH TACK INVISIBLE

SOUDAL FIX ALL HIGH TACK INVISIBLE Q 320 K9/10cm² SUPER STRONG ALL Bonding ALL Materials Surfaces MX° HYBRID POLYMER

SUPER STRONG, SUPER CLEAR HYBRID POLYMER ADHESIVE WITH HIGH INITIAL GRAB

Combine the super strong properties of High Tack with the 100% transparent appearance of Crystal, and you have our ultimate invisible bonding solution - Fix All High Tack Invisible! With a final bond strength of up to 320 kg/10 cm², outstanding initial tack, and crystal clear appearance, this product is the ultimate adhesive.

Soudal's proprietary SMX hybrid polymer technology means that this product can bond and work on virtually all materials, and even underwater.

PROPERTIES

- Super strong adhesion of up to 320 kg/10 cm² to most substrates
- 100% transparent, crystal clear appearance
- Very high tack means it can hold up very heavy loads in its initial bond!
- Extremely durable, high strength bond with superb resistance
- Retains flexibility and elasticity to accommodate movements
- Tested and certified to BRL 3107 construction adhesive specifications
- Bonds onto humid surfaces, even underwater!
- Excellent resistance to chemicals, weather, and UV
- No smell, solvent-free, isocyanate-free
- Fast curing without the need of a primer

APPLICATION

- Perfect for almost any bonding applications, especially when a very strong, invisible adhesion is required
- Any bonding involving very heavy materials
- Construction, sign-making, automotive, marine, and industrial applications

SUITABLE SUBSTRATES

Stone, Concrete, Marble, Granite, Limestone, Travertine, Cork, Rockwool, Gypsum board, Polystyrene, Glass, Mirror, Porcelain, Tiles, Brickwork, Steel, Stainless steel, Lead, Zinc, Copper, Aluminium, PVC, Polycarbonate, Wood, Timber, Plywood, MDF, Plasterboard, Fibreglass, and many more. Not suitable for PE, PP, and PTFE.

PACKAGING

290 ml cartridges, 12 cartridges / carton

COLOURS

Clear

SHELF LIFE

12 months in unopened packaging in a cool and dry place between 5°C to 25°C.

VERY HIGH INITIAL TACK

SUPER STRONG

SUPER CLEAR





10 cm²

BONDS UP TO

320 KG WITH

AREA THIS SIZE

www.soudal.com | www.soudal.com.sg