



PROFESSIONAL BUILDING PRODUCTS

GASKETSEAL

HIGH TEMPERATURE SILICONE SEALANT FOR GASKETS AND HEATING INSTALLATIONS

Gasketseal is a temperature resistant, elastic, one-component silicone sealant and replaces all cork, felt, fiber, paper and rubber gaskets in all thicknesses and widths. Its high temperature resistance of up to 285 °C ensures a problem-free application in areas like heating installations, machinery, and engines.

PROPERTIES

- Excellent resistance to fuels, oils and grease.
- High temperature resistance up to 285 °C
- Very easy to apply
- Permanent elastic after curing
- Typical acetic smell

APPLICATION

- Formation of gasket and sealing rings.
- Sealing between metal components.
- Sealing of heating installations.

PACKAGING

310 ml cartridges, 12 cartridges / carton

COLOURS

Red

SHELF LIFE

12 months in unopened packaging in a cool and dry storage place at temperatures between 5 °C to 25 °C.



-60°C to 285°C

OIL & GREASE RESISTANT

PERMANENTLY ELASTIC



EXPERTS IN SEALANTS, FOAMS, AND ADHESIVES

Soudal N.V.

Everdongenlaan 18-20,
B-2300 Turnhout, Belgium

www.soudal.com | www.soudal.com.sg



Distributed by:

PFE TECHNOLOGIES PTE. LTD.

9 Gul Street 4, Singapore 629238

T: +65 6558 6388 F: +65 6558 7310

sales@pfetec.sg | www.pfetec.sg