

SOUDAL

PROFESSIONAL CONSTRUCTION & INDUSTRIAL PRODUCTS

CHEMICAL ANCHOR CA1400

HIGH PERFORMANCE, VERY FAST-SETTING ANCHORING RESIN UP TO 1400 KG

Chemical Anchor CA1400 is a universally applicable 2-component anchoring resin for the tension-free securing of anchoring rods, studs, reinforcing bars, threaded collars, profiles etc. in structural and high-load applications, in both hollow and solid materials.

PROPERTIES

- Suitable for very heavy loads
- Very fast setting - can be exposed to loads after 30 minutes
- Withstands temperatures up to 80°C
- Easy to use and apply
- Can be applied with a standard caulking gun
- Fast cure and styrene-free (low odour)
- Can be used even in wet drill holes
- Cartridge reusable by changing static mixer (nozzle)
- Watertight and impermeable fixing

APPLICATION

- Anchoring of metal rods, threaded bolts, metal profiles etc in solid stone, brick and concrete, and hollow stones and concrete.
- Especially suited for installing, even close to edges, of hedges, banisters, shutters, fences, etc.
- Also suitable as a repair mortar for damaged concrete parts.

APPLICATION INSTRUCTIONS

Thread mixing nozzle into cartridge. Can be applied with a normal high performance cartridge gun. Application temperature 5°C and higher. Discard the first 5cm of extruded product; the colour must be homogeneously grey which indicates correct mixing of the components. Remove nozzle and reseal after use.

Installation depends on the structure; may require sleeves. For more info, please check our application guide or contact us.

PACKAGING

280 ml cartridges, 12 cartridges / carton

COLOUR

Grey



VERY STRONG ANCHORING

FAST-SETTING

EASY TO APPLY

SOUDAL

EXPERTS IN SEALANTS, FOAMS, AND ADHESIVES

SOUDAL N.V.
Everdongenlaan 18-20,
B-2300 Turnhout, Belgium
www.soudal.com | www.soudal.com.sg



Distributed by:

PFE TECHNOLOGIES PTE. LTD.
9 Gul Street 4, Singapore 629238
T: +65 6558 6388 F: +65 6558 7310
sales@pfe.tech | www.pfe.tech